



MS FOSTER

SERVING THE TRANSPORTATION INDUSTRY

1866 North Country Lane
Michigan City, IN 46360

OFFICE 219.879.9225

TOLL FREE 888.452.4053

FAX 219.879.9313

sales@msfoster.com

www.msfoster.com

Product Specification

Model No. STM7000D

The Rearview Systems STM7000D monitor features a high resolution 7.0" color display with a sunshield and a four point AMP's monitor mount. It is designed for vehicles with larger cabs. This monitor can accommodate up to three cameras and one A/V video input/output. The over-sized rubber control buttons make it easy for adjustments or programming changes, even with gloves on. The digital LED back-lit display features a bright crystal clear 337,000 pixel image. A unique feature includes our patent pending electronic adjustable rear stop line and a programmable screen brightness dimmer. This unit is ideal for truck fleets. This monitor includes: a power harness, sun visor and AMP's Mount and is protected by our Standard 5 Year Warranty.



STM-7000D



STM-7000D
with Sunshield and AMPS mount.

RVS Monitor Specification	
Model No.	STM-7000D
Video System	NTSC / PAL
LCD Panel Size	7 Inch
Resolution	800 x (RGB) x 480
LCD Brightness	450cd/m2
Screen Mode	16 : 9
LCD View Angle	40° (top), 60° (Bottom), 60° (Left), 60° (Right)
Color Configuration	RGB Stripe
LCD Dimmer	Automatic
Number Of Camera Inputs	3 Channel
Number Of Triggers	3
Multi-Display Mode	NA
Normal/Mirror	3 Channel
Audio Input	NA
Audio Output	1W Mono Speaker
External Video Input	1 Channel
Speaker Impedance	8 ohm
Camera Connector	4PinMiniDIN
On-Screen Display (OSD)	English Only Support
Operating Voltage	DC12~48V / Automatic Power On/Off by ACC
Operating Temperature	-30°C ~ 70°C -22°F ~ 158°F
Storage Temperature	-40°C ~ 80°C -40°F ~ 176°F
Power Consumption	6 Watts Max.
Dimensions	188(W) x 136.9(D) x 30(H)mm
Weight	460g
IP Rating	IP 65K
Vibration Rating	10G
Certificated	FCC

Monitor Features

- 10G Vibration Rating
- Digital High Resolution 337,000 Pixel Picture
- Adjustable on screen Distance Marker (Patent Pending)
- Accepts up to 3 Cameras, plus A/V input and output (Note: Only Cam Input 1 has Audio)
- Auto-On When Vehicle is Placed in Reverse or Started
- LED Back-lite, Low Reflection LCD
- Built-in Surge Protector
- Back-lit Control Buttons
- Contrast Control
- Brightness Control
- Built in High Fidelity Speaker
- AMPS Head Mounting System
- 5 Year Warranty

Product Specifications Subject to Change on 60 Day Notice.