FRIDER

THE MOST VERSATILE SNOW & ICE REMOVAL SYSTEM

The GVM EZ Rider is the perfect solution for surface control before and after a snow or ice event. The EZ Rider has the ability to apply granulated salt, pre-wet salt at the spinner or spray anti-icing liquids. This low clearance machine features easy maneuverability, a tight 13 foot turning radius and a front mounted light, allowing you to work into the night.

- 13 hp Briggs & Stratton electric start engine
- · Variable speed hydrostatic drive train
- · Stainless steel, rust resistant frame
- · Hydraulic spinner and agitator
- 45 PSI 3.0 GPM pump
- · Digital hour meter and tachometer
- (2) 15 gal. poly tanks, 30 gal. liquid capacity
- 250 lb granular capacity



Anti-icing before event



EZ Rider control panel



Granular salt bin





CONTACT US

1-888-452-4053

1040 HIGHWAY 212 MICHIGAN CITY, IN 46360 SALES@MSFOSTER.COM WWW.MSFOSTER.COM





POWER

The EZ Rider is powered by a 13 horsepower Briggs & Stratton engine with an electric start for quick start-up when time is valuable and results are expected immediately.

3-IN-1 VERSATILITY

Option 1: Spread granular de-icing chemicals from the powder coated hopper. The unique spinner design allows material to be spread up to 10 feet.

Option 2: Pre-wet granular chemicals at the spinner with any liquid chemical. Pre-wetting at the spinner allows the granular chemical to begin working immediately and at lower temperatures.

Option 3: Spray anti-icing liquids before or after a snow or ice event. Spray bar is located in the rear of the machine and will spread liquids up to three feet.

**After snow season is over the EZ Rider can be used to spread lime and fertilizer for landscape applications.

MANEUVERABILITY

The EZ Rider is the perfect solution for areas that require tight turning radius and "hard to get to" spots. The center pivot allows the operator to effortlessly maneuver through narrow spaces as they go about their work. The EZ Rider is small enough to fit through a 36 inch gate opening and turn in a 13 foot turning radius.

CONTROLS AND OPERATION

Easy-to-access push buttons and hand controls make the EZ Rider an extremely simple machine to operate. Forward and reverse movement is controlled by a simple hand lever.

To engage the granular portion of the spreader, simply push a lever to open the bin above the spinner. The detent lever allows for three distinct application rate settings. Pre-wetting granular material is achieved by pressing the rocker switch on the panel. To begin an anti-icing operation with liquid, just divert the flow of liquid from the spinner to a spray bar at the rear of the EZ Rider.

CONSTRUCTION

The EZ Rider is built with a stainless steel frame and powder coated hopper to provide for many years of exceptional performance, even when using the harshest corrosive de-icing chemicals.

FEATURES

The EZ Rider has a variable speed hydrostatic drive train, allowing the operator to perform their duties at safe operating speeds. The hydraulic driven spinner allows the operator to increase or decrease spinner speed as chemicals are being applied. Adjusting the spinner speed also changes the spread pattern width. Deflectors are available and can be used to limit the spread width when working in sensitive environments. The EZ Rider also features a front-mounted LED work light, providing visibility into the night.

Pump used for spraying at the spinner or anti-icing is a 3.0 gallon per minute rated pump and is ample size to achieve liquid application.

SPECIFICATIONS	
Unloaded Weight	560 lb
Liquid Loaded Weight	700 lb
Fully Loaded Weight	950 lb
Fuel Capacity	.61 gal.
Turning Radius	13 ft
Speed Forward	5 mph
Speed Reverse	2 mph
Liquid Capacity	30 gal.
Granular Capacity	250 lb
Granular Spread Pattern	3–10 ft wide
Electrical	12V battery with 13 amp charging system. Digital hour meter and tachometer.



CONTACT US

1-888-452-4053

1040 HIGHWAY 212 MICHIGAN CITY, IN 46360 SALES@MSFOSTER.COM WWW.MSFOSTER.COM

