PRODUCT INFORMATION

Description 12-24V ECE LHT Heated Low Profile

Headlight - 2 Light Kit 83.00 mm / 3.27 in 334.00 mm / 13.15 in 85.00 mm / 3.35 in

ShapeRectangularOuter Lens MaterialPolycarbonate

Outer Lens ColorClearHousing MaterialAluminumHousing ColorBlackBezel ColorBlack

Mounting Hardware Description (x2) M8-1.25 x 25mm SS Carriage Bolt

Mounting Type Universal Pedestal Mount

Retrofits Pedestal mount snow plow lights

Minimum Operating -30 °C / -22 °F

Temperature

Height

Width

Depth


Maximum Operating $55 \,^{\circ}\text{C} / 131 \,^{\circ}\text{F}$

Temperature

Connector or Wiring6-Pin Delphi (#12052848)Mating ConnectorDelphi (#12052848)

Product Weight 1.20 lbs / 0.54 kgs Shipping Weight 6.25 lbs / 2.83 kgs












1040 HIGHWAY 212 Michigan City, IN 46360

OFFICE 219.879.9225
TOLL FREE 888.452.4053
FAX 219.879.9313

sales@msfoster.com www.msfoster.com

PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS

Input Voltage 12-24V DC **Operating Voltage** 9-30V DC

Transient Spike Protection 150V Peak @ 1 HZ-100 Pulses

Red WireFront PositionBlack WireGroundWhite WireHigh BeamYellow WireLow BeamBlue WireDRL

Orange Wire Turn
Current Draw 5.00A @ 12V DC (Hi

5.00A @ 12V DC (High Beam) 3.50A @ 12V DC (Low Beam)

2.00A @ 12V DC (Front Position)

2.50A @ 12V DC (DRL) 1.20A @ 12V DC (Turn)

3.00A @ 24V DC (High Beam) 2.25A @ 24V DC (Low Beam) 1.50A @ 24V DC (Front Position)

1.75A @ 24V DC (DRL) 0.75A @ 24V DC (Turn)



1040 HIGHWAY 212 Michigan City, IN 46360

OFFICE 219.879.9225
TOLL FREE 888.452.4053
FAX 219.879.9313
sales@msfoster.com

www.msfoster.com

REGULATORY STANDARDS COMPLIANCE







Buy America Standards ECE Reg 6 ECE Reg 87 ECE Reg 112 ECE Reg 7 Eco Friendly

Tested to ECE Reg. 10 (Radiated Emissions only)

PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output 4,300 (High Beam); 2,370 (Low) **Effective Lumen** 1,060 (High Beam); 587 (Low)

Output

Candela Output 58,000


Beam Pattern(s) Forward Lighting - Daytime

Running Light

Forward Lighting - High Beam (ECE) Forward Lighting - Low Beam (ECE

Left Hand)

Signalization - Front Position Signalization - Turn (Front)



APPLICATIONS















INSTALLATION & APPLICATION INFORMATION

Each kit includes 2 lamps: a "LH" left hand lamp and a "RH" right hand lamp. This refers to installing the correct light on the left hand or right hand side of your vehicle,

Pedestal mount snow plow lights for single or double bolt mounts. Each lamp comes with mounting hardware for single bolt mount included ($1/2-13 \times 1.75$ SS Carriage Bolt with hex nut and washer), in addition to the 2 M8-1.25 x 25 SS Carriage Bolts for double bolt mounts.

SMARTHEAT™ HEATING SYSTEM

The SmartHeat™ heating system senses ambient temperature and turns the integrated heating system in the lens on & off. This system actually clears ice & snow twice as fast as conventional halogen lamps.

When does the heater turn on?

Heater turns on or off according to temperature changes and vehicle power:

- · Heater will turn on when temperatures drop, generating enough heat to prevent ice build-up.
- Heater will turn on when powering up, de-icing the light as rapidly as possible.

When does the heater turn off?

Heater will turn off when it senses temperatures increase and are above the high temperature threshold.

Learn more about this technology <u>here</u>.

See Additional Information on page 1 for heated wire installation



1040 HIGHWAY 212 Michigan City, IN 46360

OFFICE 219.879.9225
TOLL FREE 888.452.4053
FAX 219.879.9313

sales@msfoster.com www.msfoster.com

RELATED PRODUCTS





<u>Part Number</u> <u>0556273</u>

12-24V DOT/ECE RHT Heated Low Profile Headlight - 2 Light Kit



1040 HIGHWAY 212 Michigan City, IN 46360

OFFICE 219.879.9225
TOLL FREE 888.452.4053
FAX 219.879.9313
sales@msfoster.com
www.msfoster.com