


Heated Oval LED Signal Light - Model 274

PRODUCT INFORMATION

Description	12-24V DOT LED Heated White Reverse Light with Harness
Height	57.00 mm / 2.24 in
Width	165.50 mm / 6.52 in
Depth	21.00 mm / 0.83 in
Shape	Oval
Outer Lens Material	Polycarbonate
Outer Lens Color	Clear
Housing Material	Polycarbonate
Housing Color	Black
Bezel Color	Clear
Mounting Type	Grommet/Flange Bracket
Retrofits	Standard 2" x 6" Signal Lights
Minimum Operating Temperature	-40 °C / -40 °F
Maximum Operating Temperature	50 °C / 122 °F
Mating Connector	3-Pin AMP Connector (282087-1)
Product Weight	0.35 lbs / 0.16 kgs
Additional Information	Part Number Includes Wiring Harness 3270501




MS FOSTER

SERVING THE TRANSPORTATION INDUSTRY

1040 HIGHWAY 212
Michigan City, IN 46360
OFFICE 219.879.9225
TOLL FREE 888.452.4053
FAX 219.879.9313
sales@msfoster.com
www.msfoster.com


Heated Oval LED Signal Light - Model 274

PRODUCT DIMENSIONS




Pin Out Information

LIGHT (Socket shown ↑ top)




WIRE HARNESS*



*Wire harness sold separately on Part # 0346721.
Wire harness included on Part # 0346724.
Also available as a single accessory (Part # 3270501)

**To operate heating circuit on the Reverse Lamp, a separate constant 12V DC power line must be wired.



MS FOSTER

SERVING THE TRANSPORTATION INDUSTRY

1040 HIGHWAY 212
Michigan City, IN 46360
OFFICE 219.879.9225
TOLL FREE 888.452.4053
FAX 219.879.9313
sales@msfoster.com
www.msfoster.com

Heated Oval LED Signal Light - Model 274

ELECTRICAL SPECIFICATIONS

Input Voltage	10-30V DC
Operating Voltage	12-24V DC
Transient Spike Protection	150V Peak @ 1 HZ-100 Pulses
White Wire	Ground
Black Wire	Heater Only
Red Wire	Reverse
Current Draw	0.65A @ 12V DC (Reverse) 0.35A @ 24V DC (Reverse) 0.80A @ 12V DC (Heater) 0.45A @ 24V DC (Heater)

REGULATORY STANDARDS COMPLIANCE




Buy America Standards FMVSS 108 Table XII Tested to ECE Reg. 10 (Radiated Emissions only)	Eco Friendly SAE J593
--	--------------------------

APPLICATIONS



INSTALLATION & APPLICATION INFORMATION

Installation requires the black wire (for the heater) to be connected to a constant power source in order for the heater to work. Turn off power before installing.



MS FOSTER

SERVING THE TRANSPORTATION INDUSTRY

1040 HIGHWAY 212
Michigan City, IN 46360
OFFICE 219.879.9225
TOLL FREE 888.452.4053
FAX 219.879.9313
sales@msfoster.com
www.msfoster.com

Heated Oval LED Signal Light - Model 274

ACCESSORIES



Part Number
4242891
Rubber Mounting
Grommet for Model
274



Part Number
5870261
Plastic Mounting
Flange for Model 274



Part Number
8200581
Steel L-Shaped
Mounting Bracket for
Model 274



Part Number
8200591
Chrome Plastic Trim
Ring for Model 274



Part Number
3270501
3-Pin AMP Connector
(#282087-1) Wire
Harness Assembly



MS FOSTER

SERVING THE TRANSPORTATION INDUSTRY

1040 HIGHWAY 212
Michigan City, IN 46360
OFFICE 219.879.9225
TOLL FREE 888.452.4053
FAX 219.879.9313
sales@msfoster.com
www.msfoster.com

Heated Oval LED Signal Light - Model 274

RELATED PRODUCTS



Part Number
0346701
12-24V DOT LED
Heated Red Stop, Tail,
& Turn Light



Part Number
0346704
12-24V DOT LED
Heated Red Stop, Tail,
& Turn Light with
Harness



Part Number
0346711
12-24V DOT LED
Heated Amber Rear
Turn Light



Part Number
0346714
12-24V DOT LED
Heated Amber Rear
Turn Light with
Harness



Part Number
0346721
12-24V DOT LED
Heated White Reverse
Light




Part Number
0346781
12-24V DOT LED
Heated Amber Front
Position & Front Turn
Signal Light



Part Number
0346784
12-24V DOT LED
Heated Amber Front
Position & Front Turn
Signal Light with
Harness



Part Number
0346791
12-24V DOT LED
Heated Amber Side
Marker Light



MS FOSTER

SERVING THE TRANSPORTATION INDUSTRY

1040 HIGHWAY 212
Michigan City, IN 46360
OFFICE 219.879.9225
TOLL FREE 888.452.4053
FAX 219.879.9313
sales@msfoster.com
www.msfoster.com