

CALCOTE PEDESTAL SYSTEMS

PEDESTAL PRE-WET SYSTEM



GVM's Pedestal Pre-Wet Systems are multi-function liquid deicer dispensing systems designed to pre-wet truck loads of solid de-icing materials.

Pedestal Pre-Wet Systems allow users to pre-wet multiple truck loads with only one dispensing system. Pedestal systems are also capable of loading and unloading truck-mounted pre-wet tanks, returning the de-icing liquids to bulk storage tanks, and draining tanks for end-of-season maintenance.



Systems Include:

- Adjustable height spray bar
- Centrifugal pump, rated flow up to 60 GPM
- Hot dip galvanized steel to meet ASTM specification A123 on base, main body and spray arm

Options:

- Available in two models: CP-50-RC and CP-101
- Fixed base system or freestanding systems
- Storage tank sizes: 300-10,000 gal.
- Dusk-to-dawn light
- Tank Plumbing to Dispensing Package
- Post-mounted control box
- Remote control for ease of operation, remote control is standard with CP-50-RC
- Linear actuator, for mechanical spray arm adjustment
- Electric ball valve to prevent tank siphoning



MS FOSTER

SERVING THE TRANSPORTATION INDUSTRY



Built to Last

CALCOTE PEDESTAL SYSTEMS

		CP-50-RC	CP-101
Dimensions	Height	10 ft 4 in. (3.15 m)	17 ft 9 in. (5.4 m)
	Buried Depth	—	2 ft (0.61 m)
	Spray Arm Height	9 ft 4 in. (2.84 m)	7 ft 4 in. (2.24 m) - 9 ft 4 in. (2.84 m)
	Spray Head (distance from pivot)	8 ft 6 in. (2.59 m)	7 ft 10 in. (2.39 m)
	Pedestal Base	36 x 36 x 3.5 in. (L x W x H)	—
Spray Arm	Height Adjustment	Manually controlled hand winch, rated at 800 lb	
	Maximum Height over Truckloads	11 ft 3 in. (3.45 m)	
	Construction	1-½ in. galvanized steel pipe	
	Plumbing Material	Flexible PVC hose	
Spray Head	Construction	1-½ in. schedule 80 PVC	
	Nozzles	(4) brass nozzles, spaced at 15 in. interval, can be configured to meet specific needs	
	Spray Pattern	Rectangular, controlled by 1-½ in. poly ball valve connected to the inlet of the spray head	
Pump and Motor Assembly	Pump Style	Stainless steel centrifugal, 2 in. inlet, 1-½ in. outlet	
	Maximum Flow Rate	60 GPM	
	Motor Type	2 hp, 3450 rpm, TEFC 208-230 V single phase	
	Motor Housing	Rotationally molded, UV stabilized, polyethylene enclosure	
	Motor Wiring	Enclosed in LIQUITIGHT flexible conduit with LIQUITIGHT connectors at both ends	
Electric Controls	Housing	Fiberglass NEMA 4X weathertight enclosure with hinged lid, stainless steel hinged, and stainless steel lockable latch	
	External Controls	Power disconnect switch, multiple setting timer, and run/stop buttons for manual operations, located on housing cover	
	Internal Controls	Magnetic motor starter with thermal overload reset, terminal strip, relays, timers, transformer, remote control circuit board (optional), and power disconnect switch	
	Spray Cycle	0 - 120 seconds	2 - 60 seconds
	Recirculation Cycle	30 - 120 minutes	Manual on/off
	Electric Service	Customer supplied, 220 V, 20 amp, single phase required	
Plumbing	Materials	All materials used have shown proven resistance to the corrosive effects of liquid de-icers	
	Load/Unload Hoses	1 in. x 25 ft rubber hose with 1 in. poly valves and quick couple connectors	
	Valves	(2) poly 3-way valves provide directional flow to the overhead spray or load/unload hoses	
	Hose Clamps	Stainless steel	
	Serviceability	Manifold style fittings are used for many connections for quick and easy maintenance	
Options	Tank Plumbing Package	Tank to Dispensing System, includes 2 in. stainless steel tank shutoff valve, 2 in. x 15 ft flexible PVC hose with fittings, from tank to pump suction, 2 in. poly 3-way ball valve with truck fill quick couple for filling bulk storage tank from bulk delivery truck, stainless steel hose clamps, and poly hose barb fittings. Included also is a 1 in. x 10 ft hose with fittings, coupling, and valve for connection of unloading hose to storage tank.	
	Electric Ball Valve	Required when the storage tank height exceeds 10 ft., to prevent siphoning through the system when the storage tank level exceeds the spray bar height. The valve automatically opens when the pump system is activated and closes when the pump shuts off.	
	Linear Actuator	Enables overhead arm to move up and down mechanically, controlled by a two-button transmitter, to accommodate various size trucks with one pump time cycle.	
	Automatic System	Enables the arm to move up and down mechanically, controlled by a three-button transmitter, to accommodate various size trucks with two pump time cycles.	
	Remote Control	Standard	Wireless remote activates the overhead spray system
	Lighting	175 watt dusk-to-dawn light with photocell for safer evening operations	



MS FOSTER

SERVING THE TRANSPORTATION INDUSTRY

1040 Highway 212
Michigan City, IN 46360

OFFICE 219.879.9225

TOLL FREE 888.452.4053

FAX 219.879.9313

sales@msfoster.com

www.msfoster.com