



1040 Highway 212 Michigan City, IN 46360

OFFICE 219.879.9225 TOLL FREE 888.452.4053 FAX 219.879.9313

> sales@msfoster.com www.msfoster.com

Product Specification

Model No. STM7000D

The Rearview Systems STM7000D monitor features a high resolution 7.0" color display with a sunshield and a four point AMP's monitor mount. It is designed for vehicles with larger cabs. This monitor can accommodate up to three cameras and one A/V video input/output. The over-sized rubber control buttons make it easy for adjustments or programming changes, even with gloves on. The digital LED back-lit display features a bright crystal clear 337,000 pixel image. A unique feature includes our patent pending electronic adjustable rear stop line and a programmable screen brightness dimmer. This unit is ideal for truck fleets. This monitor includes: a power harness, sun visor and AMP's Mount and is protected by our Standard 5 Year Warranty.







STM-7000D with Sunshield and AMPS mount.

	ST	M-7	700)OC
--	----	-----	-----	-----

RVS Monitor Specification		
Model No.	STM-7000D	
Video System	NTSC / PAL	
LCD Panel Size	7 Inch	
Resolution	800 x (RGB) x 480	
LCD Brightness	450cd/m2	
Screen Mode	16 : 9	
LCD View Angle	40° (top), 60° (Bottom), 60° (Left), 60° (Right)	
Color Configuration	RGB Stripe	
LCD Dimmer	Automatic	
Number Of Camera Inputs	3 Channel	
Number Of Triggers	3	
Multi-Display Mode	NA	
Normal/Mirror	3 Channel	
Audio Input	NA	
Audio Output	1W Mono Speaker	
External Video Input	1 Channel	
Speaker Impedance	8 ohm	
Camera Connector	4PinMiniDIN	
On-Screen Display (OSD)	English Only Support	
Operating Voltage	DC12~48V / Automatic Power On/Off by ACC	
Operating Temperature	-30°C ~ 70°C -22°F ~ 158°F	
Storage Temperature	-40°C ~ 80°C -40°F ~ 176°F	
Power Consumption	6 Watts Max.	
Dimensions	188(W) x 136.9(D) x 30(H)mm	
Weight	460g	
IP Rating	IP 65K	
Vibration Rating	10G	
Certificated	FCC	

Monitor Features

- 10G Vibration Rating
- Digital High Resolution 337,000 Pixel Picture
- Adjustable on screen Distance Marker (Patent Pending)
- Accepts up to 3 Cameras, plus A/V input and output (Note: Only Cam Input 1 has Audio)
- Auto-On When Vehicle is Placed in Reverse or Started
- LED Back-lite, Low Reflection LCD
- Built-in Surge Protector
- Back-lit Control Buttons
- Contrast Control
- Brightness Control
- Built in High Fidelity Speaker
- AMPS Head Mounting System
- 5 Year Warranty